



INVESTOR IN PEOPLE

USA

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was subsequently filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

AmBrewster

Dated 5 September 2003

OLIFF & BERRIDGE, PLC
P.O. BOX 19928
ALEXANDRIA, VA 22320
(703) 836-6400
APPLICANT: Jonathan J. MORGAN
APPLICATION NO.: New U.S. Application
FILED: October 27, 2003
FOR: SEALING ARRANGEMENT
ATTORNEY DOCKET NO.: 117533

Patents Form 1/77

Patents Act 1977
(Rule 16)15NOV02 E763819-1 001097
POL/7700 0.00-0226685.6**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference PAT/AT/3042

2. Patent application number
(The Patent Office will fill in this part)

0226685.6

15 NOV 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ROLLS-ROYCE plc
65 BUCKINGHAM GATE
LONDON
SW1E 6AT
GREAT BRITAIN

Patents ADP number (if you know it)

3970002

If the applicant is a corporate body, give the country/state of its incorporation

GREAT BRITAIN

4. Title of the invention SEALING ARRANGEMENT

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

MR V J BIRD
INTELLECTUAL PROPERTY DEPT WH 5B
ROLLS-ROYCE plc
PO BOX 3
FILTON
BRISTOL
BS34 7QE

Patents ADP number (if you know it)

3970005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, orc) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 12

Claim(s) 4

Abstract 1

Drawing(s) 6

only for

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

YES

Request for preliminary examination and search (Patents Form 9/77)

YES

Request for substantive examination (Patents Form 10/77)

NO

Any other documents (please specify)

NO

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

V J BIRD

15 NOVEMBER 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

ADAM TINDALL 0117 979 4623
adam.tindall@rolls-royce.com

Warning


After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

Patents Form 7/77

Patents Act 1977
(Rule 15)Statement of inventorship and of
right to grant of a patent

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference PAT/AT/3042

2. Patent application number
(if you know it)

0226685.6

115 NOV 2002

3. Full name of the or of each applicant ROLLS-ROYCE plc

4. Title of the invention

SEALING ARRANGEMENT

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patent.BY VIRTUE OF THE INVENTORS' TERMS AND CONDITIONS OF
EMPLOYMENT6. How many, if any, additional Patents Forms
7/77 are attached to this form? NO
(see note (c))

7.

I/We believe that the person(s) named over the page (and on
any extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to.

Signature

Date

V J BIRD

15 NOVEMBER 2002

8. Name and daytime telephone number of
person to contact in the United KingdomADAM TINDALL 0117 979 4623
adam.tindall@rolls-royce.com

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

JONATHAN JAMES MORGAN
40 DON BOSCO CLOSE
TEMPLE COWLEY
OXFORD
OX4 2LD

758 01 29002

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents Form 7/77

- 1 -

SEALING ARRANGEMENT

The invention is a sealing arrangement. In particular it refers to a sealing arrangement for turbo machinery.

The sealing arrangement can be employed to maintain a seal in any suitable rotating machinery including, but not limited to, gas turbine engines.

In a conventional gas turbine engine, a fan is used for pressurising ambient air which is then passed downstream to a compressor to be further compressed. The air is then mixed with fuel in a combustor, ignited and burned to expand the gas, increasing the gas temperature. Energy is extracted from the gas by passing it through a turbine prior to being exhausted. The engine may have a high pressure turbine which powers the compressor, and a low pressure turbine which powers the fan.

The rotatable sections of an engine typically comprise annular arrays of large fan blade rotors and smaller compressor and turbine rotor blades, the blades normally being interspaced with annular arrays of static aerodynamic guide vanes (commonly referred to as stator vanes). Each set of rotor blades and stator vanes is referred to as a stage. The stator vanes ensure the gas impinges on the rotor at the correct angle. In the turbine section in some types of engine they also serve to increase the velocity and reduce the pressure of the gas.

The rotatable components extend radially outward from supporting discs or drums which are fixedly joined to a shaft and are rotatable about the axis of the shaft. The shaft may vary in diameter along its length and may comprise radial extensions in order to interface with a component such as a seal.

Hereinbefore and hereafter a radial direction is taken to mean direction perpendicular to the longitudinal axis of the rotor, and an axial direction is taken to mean a direction parallel to the longitudinal axis of the rotor.

- 2 -

Concentric alignment and rotatable support of the shaft and other rotatable components within a surrounding casing is maintained by bearings, which are in communication with the engines static support structure. The bearings also act as a means to transmit vibratory, aerodynamic and centrifugal loads into the engine support structure. During normal operation the rotating components are dynamically balanced.

The compressor and turbine stator vanes remain stationary relative to the rotors and so are normally fixedly joined to the compressor or turbine casings respectively. To enable the engine to operate efficiently, the gas path through the engine must be sealed to prevent losses through leakage. Hence the stators must seal against the drums of the compressor and turbine effectively so that gas being worked only travels down the desired gas path.

There are a number of interfaces between rotatable and static surfaces that require sealing. Typically sealing is required at fan exit; at the inter stage of the intermediate and high pressure compressor; at the high pressure compressor discharge location; at the high pressure turbine pre-swirl position and the low and intermediate pressure turbine inter stage locations. This list is not exhaustive. Sealing is required at any air-to-air sealing location where a reduction in leakage results in a performance benefit.

An air seal can be achieved by the use of a labyrinth seal. These are not designed to form a physical barrier, but rather to form a tortuous route for the air such that there is a controlled but minimal leakage through the seal.

Another solution is the use of segmented seals, which adapt to conform about a rotating shaft. However, the pressure differential across the seal face may force the segments against their housing, reducing their mobility and hence reducing their sealing efficiency.

Both the aforementioned seals are prone to leakage when there are large radial shaft or drum movements and the shaft and seal may be damaged if the displacement is

- 3 -

large enough. Likewise seals employing piston ring type sealing arrangements may get locked into position by wear or abuse.

Brush seals are also employed and although they offer an improvement in sealing, they have not seen wide spread use in "heavy duty" sealing applications within gas turbine engines. One problem with brush seals is that the pressure differential across the bristle pack compresses the bristle pack axially against the backing plate of the seal.

As a result the bristles wear quickly and ultimately the brush seal performs poorly, acting in effect as a single fin labyrinth seal.

According to the present invention there is provided a sealing arrangement for sealing a leakage gap between relatively moveable parts in a flow path between a region of high fluid pressure and a region of low fluid pressure comprising a sealing member having an upstream surface, a downstream surface, a radially outer surface and a radially inner surface, said sealing member being in communication with a housing via resilient means wherein the resilient means is fixedly joined to the upstream surface of the sealing member such that during operation both the radial force induced on the sealing member by fluid flowing axially into and circumferentially over the radially inner surface and the axial force induced on the sealing member because of a pressure difference across the sealing member is resisted by the resilient means.

Preferably the radially inner surface of the sealing member is provided with a plurality of channels passing from the upstream surface to the downstream surface.

The invention provides a seal between two volumes at different pressures in rotatable machinery. As previously mentioned, one location where sealing is required is the interface between a static structure and a rotatable surface. The interface between a stator vane and a compressor rotor or turbine rotor (sometimes referred to as a compressor drum or turbine drum) is one such location.

The sealing arrangement comprises a ring of sealing members, which may be continuous or segmented. Said segments may interconnect or simply abut one

another. The sealing arrangement comprises a housing rigidly fixed to, in this example, the stator and located at the interface between the stator and the rotor. The housing provides support and location for a resilient means, such as a sprung cantilever. The resilient means in turn supports a sealing member. A large pressure drop across the sealing arrangement will induce large axial forces on the sealing member. The resilient means provides axial support for the sealing member, thereby preventing the sealing member from becoming forced and locked against the downstream side of the housing.

The radially inner surface of the sealing member is configured such that, in operation, it generates hydrodynamic lift. It does this by retaining fluid in a small clearance volume between the radially inner surface and the rotors. This is referred to as hydrodynamic lubrication or "air riding". The retained fluid provides an air seal between the two volumes whilst also preventing wear of the adjacent surfaces.

The lift generated by the air riding geometry may need to be supplemented at low shaft speeds by ventilation passages that allow fluid at upstream pressure to ventilate the sealing members radially inner surface, thus providing additional hydrostatic lift.

The device is particularly suited to "high duty" sealing requirements in rotating machinery where differential pressures, relative radial movements and relative surface speeds are high. Hydrodynamic lift will increase as the relative speed between the radially inner surface and rotor is increased, resulting in a stiffer film of air being generated. This will help to prevent contact between the sealing member and the rotor during transient movements. At steady state high speed conditions there may be a tendency for a larger than desired clearance which may result in higher leakage. However the leakage will still be low compared to a conventional seal.

The invention and how it may be constructed and operated, will now be described in greater detail with reference, by way of example, to an embodiment illustrated in the accompanying drawings, in which:

- 5 -

Figure 1 is a pictorial representation of a cross section of a typical gas turbine engine incorporating a sealing arrangement in accordance with the present invention.

Figure 2 is a pictorial representation of a typical interface between a static stator vane and rotatable drum incorporating a sealing arrangement in accordance with the present invention.

Figure 3 shows an enlarged view of a sealing arrangement.

Figure 4 is an alternative view of the sealing arrangement, showing a radially inner surface.

Figure 5 shows an enlarged view of the radially inner surface.

Figure 6 is a cross sectional view of the radially inner surface

Figure 7 shows a possible form of interconnecting segments as they would appear at the interface between the sealing arrangements housing and the static support structure.

Figure 8 shows a wedge shaped profile on the radially inner surface.

Figure 9 shows a flange formed on the radially inner surface.

Figure 10 shows passages exhausting to the radially inner surface.

Figure 11 shows passages exhausting to the radially inner surface.

Figure 12 shows an alternative embodiment of the radially inner surface configuration.

Figure 13 shows a further alternative embodiment of the radially inner surface configuration.

Figure 1 illustrates the main sections of a gas turbine engine 2. The overall construction and operation of the engine 2 is of a conventional kind, well known in the field, and will not be described in this specification beyond that necessary to gain an understanding of the invention. For the purposes of this description the engine is divided up into five sections—a fan section 4; a compressor section 6, a combustor section 8 and a turbine section 10, collectively known as the "engine core"; and a bypass section 12. The compressor 6 and turbine 10 comprise stator vanes 14 and rotor blades 16, 17 respectively. Air, indicated generally by arrow "A", enters the engine 2 via the fan section 4, constrained on one side by an outer wall 18 and on the other by a discontinuous inner wall 20. Support for the inner wall 20 and the engine core is provided by an array of support members 22 which extend radially towards, and are in communication with, the outer wall 18. The inner wall 20 comprises several static and rotatable sections, the details of which are not required here to appreciate the invention. The air is compressed and the airflow is split, passing downstream through the bypass 12 and to the compressor 6, as indicated generally by "B" and "C" respectively. The air is further pressurised by the compressor 6, a proportion of which enters the combustion section 8, the remainder of the air being employed elsewhere. Fuel is injected into the combustor airflow, which mixes with air and ignites before exhausting out of the rear of the engine via the turbine section 10.

In this embodiment the low pressure rotor blades 16 in the compressor 6 and turbine 10 are fixedly joined to form a low pressure rotor drum 26. The fan blades 24 and low pressure drum 26 are fixedly joined to a first shaft 30 that is rotatable about the central axis of the engine 2. Likewise the high pressure rotor blades 17 in the compressor 6 and turbine 10 are fixedly joined to form a high pressure drum 28, which are fixedly joined to a second shaft 32 that is rotatable about the central axis of the engine 2 and is coaxial with the first shaft 30.

The first shaft 30 is rotatably supported by bearings 34 at the upstream end of the shaft and by bearings 36 at the downstream end. First and second static members 38 and

- 7 -

40 support the bearings 34 and 36 respectively, which are in communication with a static section of the inner wall 20. The second shaft 32 is rotatably supported by bearings 42 at the upstream end of the shaft and by bearings 44 at the downstream end. A sealing arrangement 46 is fixedly attached to the inner diameter of the second shaft 32 between said bearings 42 and 44. A sealing arrangement 48 is fixedly attached to stator vanes 14.

Presented in Figure 2 is an enlarged view of the interface between the sealing arrangement 48 and the turbine stator vane 14, which, in this embodiment, acts as a static support structure 50. The sealing arrangement 48 is disposed around a first rotatable member 52 and joined to said static support structure 50. The first rotatable member 52 represents any rotatable surface, such as the low pressure rotor drum 26 or the high pressure rotor drum 28. The details of how the sealing arrangement 48 is joined to the static support structure 50 are not key to understanding the operation of the sealing arrangement 48. Relative to the sealing arrangement 48 there is a region of high pressure upstream and a region of relatively low pressure downstream, indicated by "D" and "E" respectively.

A further enlarged view of the sealing arrangement 48 is presented in Figures 3 and 4. For clarity the static support structure 50 is not shown.

The sealing arrangement 48 comprises a housing 54 fixedly joined to a resilient means 56 which is in turn in communication with a sealing member 58 having an upstream surface 60, a downstream surface 62, a radially outer surface 64 and a radially inner surface 66. The sealing member 58 is provided with a plurality of channels 68 passing from the upstream surface 60 to the downstream surface 62 across the radially inner surface 66.

As presented in figure 5, the channels 68 are formed on the radially inner surface 66 such that they have at least one change of direction. "D" and "E" indicate the upstream and downstream sides of the sealing member 58 respectively.

The channels 68 have a right-angled cross section, as shown in figure 6. The channels 68 have a depth "d" in the range of about 0.5µm to 10 µm and a width "w" in the range of about 0.1 mm to 15mm with an adjoining land "v" approximately one third of the channel width. The precise dimensions will depend upon the desired hydrodynamic film thickness.

The sealing member 58 is provided with at least one ventilation passage 70 which extends from the upstream surface 60 to the radially inner surface 66. The downstream surface 62 of the sealing member 58 is provided with a sealing means 72. The sealing means 72 is formed as a radially resilient ring located in a circumferential groove 73 provided in the housing 54. In operation the sealing means 72 is in sliding contact with the housing 54 and the sealing member 58. In an alternative embodiment the sealing means 72 is formed as a discontinuous ring, sometimes referred to as a split ring. The sealing means 72 is selected from at least one of a group of materials comprising steel alloys, nickel alloys, bronze, carbon graphite, silicon nitride, silicon carbide, zirconia, alumina, zialon and stellite. It would be appreciated by a man skilled in the art that this list is not exhaustive.

There is also provided a sealing device 76 positioned upstream of the sealing means 72 and generally radially directed, creating a seal between the housing 54 and the sealing member 58 and a chamber indicated generally by "F". The precise configuration of the sealing device 76 is not important, but it may take the form of labyrinth seal, with inner and outer annular flanges 78 and 80 respectively in communication with the housing 54 and the sealing member 58 respectively. The flanges 78 and 80 are configured such that despite any relative radial movement between the housing 54 and the sealing member 58 a tortuous route is provided such that there is a controlled but minimal leakage through the seal. This ensures that the chamber "F" remains at a slightly lower pressure than the air upstream of the sealing device 76. With this arrangement the sealing member 58 is free to ride on the film of air trapped by the radially inner surface 66 and not inhibited by high pressure air forcing the sealing member 58 towards the first rotatable member 52.

As previously described the sealing arrangement 48 is formed as a ring and disposed around a first rotatable member 52. The ring may be continuous or divided into segments for ease of installation. Each segment can simply abut the other or, as shown the view of the external diameter of the ring in figure 7, is formed as interconnecting segments 82, thereby providing a tortuous fluid leakage route such that there is a controlled but minimal leakage through the seal.

The resilient means 56, sealing device 76, sealing means 72, housing 54 and sealing member 58 may each be formed as a continuous ring or comprise a series of simply abutted or interconnecting segments. Additionally, per segment, the resilient means 56 may be formed out of one or more elements.

In operation the seal between the high fluid pressure region D and the low fluid pressure region E is maintained by fluid retained in the small clearance volume 84 between the radially inner surface 66 and the first rotatable member 52. Studies to date indicate that optimum performance is achieved by maintaining a clearance 84 greater than about 1µm but less than about 5µm. The channels 68 are configured such that air is "scooped" into the clearance volume 84 where it has significant residence time, forming an hydrodynamic or "air riding" seal.

It is imperative that the radially inner surface 66 be maintained. In operation, during startup or shutdown or when at rest, the radially inner surface 66 may contact the first rotatable member 52. To prevent erosion the radially inner surface 66 may be provided with an erosion resistant coating or surface treatment, selected from at least one of a group of materials comprising nitrided steel, carburised steel, hard anodised aluminium, tungsten carbide, chrome carbide, titanium carbide, titanium nitride. It would be appreciated by a man skilled in the art that this list is not exhaustive.

If the clearance 84 increases because of relative radial movement between the radially inner surface 66 and the first rotatable member 52, the film pressure generated in the clearance 84 will fall resulting in a radially inward displacement of the sealing member 58. Conversely if the clearance 84 increases because of relative radial movement

- 10 -

between the radially inner surface 66 and the first rotatable member 52 the pressure generated in the clearance 84 increases thus forcing the sealing member 58 to move outwards.

Relative radial displacements of the static support structure 50 and the first rotatable surface 52 may lead to unfavourable increases in the clearance 84. Additionally the radial forces generated on the radially inner surface 66 as a result of the hydrodynamic lift may also act to unfavourably affect the clearance 84. The resilient means 56 provides radial support for the sealing member 58, thereby controlling the clearance 84.

In order to maintain the clearance 84 to within acceptable limits during operation, the radial resilience of the resilient means 56 is balanced against the radially outward force generated by the hydrodynamic film in clearance 84. The resilient means 56 is configured such that when the relative speed between the radially inner surface 66 and the first rotatable member 52 is substantially zero the radially inner surface 66 abuts or is in close proximity to the first rotatable member 52. Additionally the resilient means 56 is configured such that when the relative speed between radially inner surface 66 and the first rotatable member 52 is low the radially outward force produced by the hydrodynamic film pressure is sufficient to counteract the radially inward force of the resilient means 56, thereby maintaining the clearance 84. Additionally the resilient means 56 is configured such that when the relative speed between radially inner surface 66 and the first rotatable member 52 is high the resilient means 56 counteracts the radially outward force to such a degree that the clearance 84 is maintained.

Additionally the resilient means 56 is configured such that it resists axial force induced on the sealing member 58 because of a pressure difference across the sealing member 58. In this way the sealing member 58 is prevented from becoming forced and locked against the housing 54.

In order to provide additional lift at low shaft speeds the radially inner surface 66 of the sealing member 58 is formed such that in operation a clearance 84 is maintained between the first rotatable member 52 and the radially inner surface 66 which is larger

- 11 -

at the upstream end of the sealing member 58 than it is at the downstream end, forming a wedge shaped interspace 86, as shown in figure 8.

Alternatively, as shown in figure 9, a circumferential flange 88 is provided substantially towards the downstream end of the radially inner surface 66 of the sealing member 58, forming a rectangular shaped interspace 90.

In both of the above described embodiments the interspace 86,90 ensures that even at zero or very low shaft speeds a clearance 84 is provided between the between the radially inner surface 66 and the first rotatable member 52. The interspace 86,90 is filled with air from the high pressure region "D" which forms a hydrodynamic film, thereby producing lift and exerting a radial outward force on the sealing member 58.

The lift generated by the radially inner surface 66 may need to be supplemented when the relative speed of the radially inner surface 66 and the first rotatable member 52 is low. The ventilation passages 70 allow the communication of fluid from the high pressure region D to the radially inner surface 66, thereby providing additional hydrostatic lift. Additionally the passages 70 may contain restrictions to limit the flow of air at higher relative speeds, thus minimising the clearance 84 and maximising sealing performance at a design condition. The passages 70 terminate on the radially inner surface 66 along a common circumferential line, as shown in figure 10. Alternatively, as shown in figure 11, the passages 70 may be configured to terminate on the radially inner surface 66 in a less regular order.

In an alternative embodiment the channels 68 formed on the radially inner surface 66 of the sealing member 58, as presented in figure 12, are provided at an angle to the axial direction of the sealing plane.

In a further alternative embodiment, as presented in figure 13, the channels 68 are provided with an arcuate form at an angle to the axial direction of the sealing plane.

- 12 -

The sealing arrangement 48 can be used to maintain a seal in any rotating machinery including, but not limited to gas turbine engines.

The configurations shown in Figures 1 to 13 are diagrammatic. The design and positioning of the sealing arrangement, rotor blades, bearings, fan casing and other parts may vary. Likewise the combination and configuration of these components will vary between designs.

CLAIMS

1. A sealing arrangement for sealing a leakage gap between relatively moveable parts in a flow path between a region of high fluid pressure and a region of low fluid pressure comprises a sealing member having an upstream surface, a downstream surface, a radially outer surface and a radially inner surface, said sealing member being in communication with a housing via resilient means

wherein the resilient means is fixedly joined to the upstream surface of the sealing member such that during operation both the radial force induced on the sealing member by fluid flowing axially into and circumferentially over the radially inner surface and the axial force induced on the sealing member because of a pressure difference across the sealing member is resisted by the resilient means.
2. A sealing arrangement as claimed in claim 1 wherein said radially inner surface of the sealing member is provided with a plurality of channels passing from the upstream surface to the downstream surface.
3. A sealing arrangement as claimed in claim 2 wherein the channels have a depth in the range of about 0.5µm to 10 µm and a width in the range of about 0.1 mm to 15mm with an adjoining land approximately one third of the channel width.
4. A sealing arrangement as claimed in claims 2 or 3 wherein said plurality of channels have at least one change of direction.
5. A sealing arrangement as claimed in claims 2 to 4 wherein said plurality of channels are arcuate.

- 14 -

6. A sealing arrangement as claimed in claims 1 to 5 wherein said resilient means is formed as a cantilever.
7. A sealing arrangement as claimed in claims 1 to 6 wherein said housing is formed as a ring.
8. A sealing arrangement as claimed in claim 1 to 7 wherein said sealing arrangement is divided into a plurality of segments.
9. A sealing arrangement as claimed in claim 1 to 8 wherein said sealing arrangement is divided into a plurality of interconnecting segments.
10. A sealing arrangement as claimed in claim 8 and claim 9 wherein the resilient means is formed out of one or more elements per segment.
11. A sealing arrangement as claimed in claim 1 to 10 wherein the said sealing arrangement is disposed around a first rotatable member and fixedly joined to a static support structure.
12. A sealing arrangement as claimed in claim 11 wherein said first rotatable member is a shaft.
13. A sealing arrangement as claimed in claim 11 wherein said first rotatable member is a drum.
14. A sealing arrangement as claimed in claims 11 to 13 wherein during operation a clearance is maintained between the sealing member and the first rotatable member.
15. A sealing arrangement as claimed in claim 14 wherein the clearance is greater than about $1\mu\text{m}$ but less than about $5\mu\text{m}$.

- 15 -

16. A sealing arrangement as claimed in claims 11 to 14 wherein the radially inner surface of the sealing member is formed such that in operation a clearance is maintained between the first rotatable member and the radially inner surface which is larger at the upstream end of the sealing member than it is at the downstream end.
17. A sealing arrangement as claimed in claims 11 to 14 wherein a circumferential flange is provided substantially towards the downstream end of the radially inner surface of the sealing member.
18. A sealing arrangement as claimed in claims 1 to 17 wherein the resilient means is configured such it produces a radially inward force on the sealing member which increases as the clearance between the radially inner surface of the sealing member and the first rotatable member increases.
19. A sealing arrangement as claimed in claims 1 to 18 wherein the sealing member is pierced providing at least one passage which extends from the upstream surface to the radially inner surface.
20. A sealing arrangement as claimed in claim 19 wherein the sealing member is configured such that the air passing through the at least one passage induces a radially outward displacement of the sealing member.
21. A sealing arrangement as claimed in claims 1 to 20 wherein a sealing means is provided between the downstream surface of the sealing member and the housing.
22. A sealing arrangement as claimed in claim 21 wherein the sealing means is formed as a radially resilient ring located in a circumferential groove provided in the housing such that in operation the sealing means is in sliding contact with the housing and the sealing member.

- 16 -

23. A sealing arrangement as claimed in claims 21 and claim 22 wherein the sealing means is formed as a discontinuous ring.
24. A sealing arrangement as claimed in claims 21 to 23 wherein the sealing means is selected from at least one of a group of materials comprising steel alloys, nickel alloys, bronze, carbon graphite, silicon nitride, silicon carbide, zirconia, alumina, zialon and stellite.
25. A sealing arrangement as claimed in claims 1 to 24 wherein a sealing device is provided between the housing and the sealing member, said sealing device being positioned upstream of the downstream surface.
26. A sealing arrangement as claimed in claim 25 wherein the sealing device has a upstream surface and a downstream surface and provided with radially extending flanges in communication with the housing and the sealing member configured such that a tortuous route is provided between the upstream surface and the downstream surface of the sealing device such that there is a controlled but minimal leakage through the sealing device.
27. A sealing arrangement as claimed in claims 1 to 26 wherein the radially inner surface of the sealing member is provided with an erosion resistant surface.
28. A sealing arrangement as claimed in claim 27 wherein the radially inner surface of the sealing member is coated with at least one of the materials selected from a group comprising nitrided steel, carburised steel, hard anodised aluminium, tungsten carbide, chrome carbide, titanium carbide, titanium nitride.
29. A sealing arrangement as claimed in any preceding claim for use in a gas turbine engine.
30. A sealing arrangement substantially as hereinbefore described with reference to the accompanying drawings.

- 17 -

ABSTRACT**SEALING ARRANGEMENT**

A sealing arrangement for sealing a leakage gap between relatively moveable parts in a flow path between a region of high fluid pressure and a region of low fluid pressure comprises a sealing member having an upstream surface, a downstream surface, a radially outer surface and a radially inner surface, said sealing member being in communication with a housing via resilient means. The resilient means is fixedly joined to the upstream surface of the sealing member such that during operation both the radial force induced on the sealing member by fluid flowing axially into and circumferentially over the radially inner surface and the axial force induced on the sealing member because of a pressure difference across the sealing member is resisted by the resilient means.




FIGURE 1









FIGURE 2








FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13

